

300Mbps Wireless N 4G LTE Router Model: MB110-4G



//Highlights



SIM Card Plug and Play



Connect up to 32 Devices[†]



4G(TDD&FDD) /3G Compatible





Superfast 4G LTE Speed for Reliable Wi-Fi

and stable connections to every device.

Amplifier boost sending and receiving

capabilities, creating a wide-coverage

Power Amplifier and Low Noise

Wi-Fi network for your home.

Working as a 4G router, the MB110-4G uses 4G LTE technology to achieve super fast speeds up to 150 Mbps download and 50 Mbps upload. It can also share a Wi-Fi network with maximum speed of 300 Mbps on 2.4 GHz for gaming, streaming, and more.



Connect up to 32 wireless devices

with ease while ensuring depend-

able network stability.

With a fully functional WAN/LAN port, MB110-4G can work as a router which is compatible with cable, fiber, and DSL modems.

MERCUSYS°

Specifications

Hardware

• LTE:

Download Speed 150 Mbps +Upload Speed 50 Mbps[‡]

• Ports:

1× 10/100 Mbps LAN/WAN +1× 10/100 Mbps LAN 2×4G/3G External Antenna Ports

- Antennas:
 2 Internal 4G LTE Antennas
- Dimensions: 3.5×3.5×5.9 in (90×92×150.5 mm)
- External Power Supply: 9V/0.85A



Wireless

- Network Type (EU):
 4G: FDD-LTE B1/B3/B5/B7/B8/B20/B28
 (2100/1800/850/2600/900/800/700 MHz)
 TDD-LTE B38/B40 (2600/2300 MHz)
 3G: HSPA+/HSPA/UMTS B1/B5/B8 (2100/850/900 MHz)
 Network Type (UN):
 4G: FDD-LTE B1/B2/B3/B4/B5/B7/B8/B28/B66
 (2100/1900/1800/1700/850/2600/900/700/1700 MHz)
 TDD-LTE B40 (2300MHz)
 3G: HSPA+/HSPA/UMTS B1/B2/B4/B5/B8(2100/1900/1700/850/900 MHz)
 Wireless Standards: IEEE 802.11b/g/n
 Frequency: 2.4 GHz
 Signal Rate: 300 Mbps
 EIRP (CE): < 20 dBm (2.4 GHz)
 Reception Sensitivity:
- 11g 54M: -74dBm
- 11N HT20 MCS7: -73dBm
- 11N HT40 MCS7: -70dBm
- Wireless Function:

Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics

• Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK encryptions

MERCUSYS°

Specifications

Software

- Operating Modes:
 3G/4G Router, Wireless Router
- WAN Type: Dynamic IP/Static IP/PPPoE/PPTP(Dual Access)/L2TP(Dual Access)
- DHCP: Server, DHCP Client List, Address Reservation
- Port Forwarding: ALG, Virtual Server, Port Triggering, UPnP, DMZ
- Dynamic DNS: DynDns, NO-IP
- Security: IPv4 SPI Firewall, IP and MAC Address Binding
- Protocols: IPv4, IPv6
- Management: Local Management, Remote Management
- Administration:
- Upgrade Firmware, Factory Default, System Log, Diagnostic Tools
- Guest Network:
- 2.4 GHz Guest Network

© 2023 MERCUSYS

†Maximum wireless signal rates are the physical rates derived from IEEE Standard 802.11 specifications. Actual wireless data throughput and wireless coverage, and quantity of connected devices are not guaranteed and will vary as a result of network conditions, client limitations, and environmental factors, including building materials, obstacles, volume and density of traffic, and client location.

#Maximum 4G download speeds depend on external factors such as the local 4G network coverage, data plan, real-time network capacity, client limitations, and environmental factors.

Others

- Certification:
- CE, RoHS
- Requirements:
 Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other
 JavaScript-enabled browser
 Nano SIM Card
- Environment: Operating Temperature: 0°C~40°C (32°F ~104°F)
- Package Contents
 300 Mbps Wireless N 4G LTE Router MB110-4G
 Power Adapter
 RJ45 Ethernet Cable
 Quick Installation Guide