

DH-PFS3005-5GT

Unmanaged Desktop Switch



- Plug and play: No configuration required
- Robust design: 24/7 stable performance in operating temperature from 0°C to 40°C
- Optimized performance: Provides full-speed transmission in all ports simultaneously
- Flexible deployment: Supports desktop and wall mount



Plug & Play



Robust Design



Optimized Performance



Easy Installation

Functions

Full Gigabit Ports

Equipped with 5 10/100/1000 Mbps ports enable fast transmission for your network, ideal for home and small office scenario.

Silent Operation

Designed with durable metal casing and fanless structure, ensure the heat dissipation during a noiseless operation.

Easy Installation

Both deployment and settings are designed to make a hassle-free experience for our customers, while providing an optimal operation.

Scene



Home



Shop



Dormitory



Meeting Room

Technical Specification

Performance

Layer	Layer 2
-------	---------

Hardware

Standard Power Supply	Yes
Ethernet Port	4
Ethernet Port Rate	1000 Mbps
Power Supply	5V/600mA DC
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	10%–90% (RH)
Storage Temperature	-20°C to +70°C (-4°F to +158°F)
Storage Humidity	10%–90% (RH)
Power Consumption	< 3W

Performance

Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
Packet Buffer Memory	1 Mbit
MAC Table Size	2K
Standards Compliance	IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE802.3az

General

ESD	Air discharge: 8kV Contact discharge: 6kV
Thunderproof	Common mode: 2kV
Net Weight	195 g (0.43 lb)
Dimensions	100 mm × 65 mm × 22.6 mm (3.94" × 2.56" × 0.88") (L × W × H)

Dimensions (mm[inch])

